

Standard Dimensions, Nordic Lam

STANDARD DIMENSIONS (Metric Units)

Product:	Nordic Lam Architectural 24F/ES12						
Width (mm):	44	86	137	184	228	279	327
Depths (mm):	70	127					
	95	178	178				
	121	222	222	222			
	146	267	267	267	267		
	171	318	318	318	318	318	
	197	362	362	362	362	362	362
	222	406	406	406	406	406	406
	248	457	457	457	457	457	457
	273	502	502	502	502	502	502
	298	546	546	546	546	546	546
	324	597	597	597	597	597	597
	349	641	641	641	641	641	641
	375	686	686	686	686	686	686
	400	737	737	737	737	737	737
	425	781	781	781	781	781	781
	451	826	826	826	826	826	826
		870	870	870	870	870	870
		921	921	921	921	921	921
		965	965	965	965	965	965
		1010	1010	1010	1010	1010	1010
			1054	1054	1054	1054	1054
			1105	1105	1105	1105	1105
			1149	1149	1149	1149	1149
			1194	1194	1194	1194	1194
			1245	1245	1245	1245	1245
			1289	1289	1289	1289	1289
			1334	1334	1334	1334	1334
			1384	1384	1384	1384	1384
			1429	1429	1429	1429	1429
			1473	1473	1473	1473	1473
			1499	1499	1499	1499	1499
			1568	1568	1568	1568	1568
			1613	1613	1613	1613	1613
			1664	1664	1664	1664	1664
			1708	1708	1708	1708	1708
			1753	1753	1753	1753	1753
			1797	1797	1797	1797	1797
			1848	1848	1848	1848	1848
			1892	1892	1892	1892	1892
			1937	1937	1937	1937	1937
			1981	1981	1981	1981	1981
			2032	2032	2032	2032	2032
			2076	2076	2076	2076	2076
			2121	2121	2121	2121	2121
			2172	2172	2172	2172	2172
				2216	2216	2216	2216
				2261	2261	2261	2261
				2311	2311	2311	2311
				2356	2356	2356	2356
				2400	2400	2400	2400

Notes:

1. The depth-to-width ratio shall be limited to 12:1.
2. The dimensions showed in black are the optimum dimensions for straight beams (maximum length of 18.9 m).
3. Beams of dimensions in light grey are fabricated using manual techniques (maximum length of 24.4 m).
4. Arched beams are available in dimensions up to 327 mm x 2400 mm x 24 m (width x depth x length).
5. Other dimensions are available on request; please contact Nordic.